

HDPE green tank

300 - 15 000 L

TANK



▶ To store water, liquid fertiliser, foods, etc.

BENEFITS

- Anti-UV treatment
- In high density polyethylene
- Seamless single block
- Resistant to products with a density up to 1300 kg/m³
- Can be buried
- Can be fitted in a skip or on a frame
- 2" front outlet and rear outlet



Unique on the market

DENSITY UP TO 1300 KG/M³

TECHNICAL CHARACTERISTICS

Reference	Capacity in L	Dimensions L x W x H in mm	Manhole diameter in mm	Weight in kg	Plastic valve
01011300036	300	1120 x 650 x 600	450	21	1" 1/4
01011300037	500	1850 x 650 x 600	450	29	1" 1/4
01011300038	1200	1960 x 980 x 900	450	60	2"
01011300039	1700	2710 x 980 x 900	450	82	2"
01011300040	2750	2360 x 1330 x 1300	450	91	2"
01011300041	3500	2960 x 1330 x 1300	450	127	2"
01011300042	5000	2840 x 1600 x 1550	680	250	2"
01011300043	6500	3640 x 1600 x 1550	680	285	2"
01011300044	7500	4050 x 1600 x 1550	680	377	2"
01011300046	10,000	2800 x 2240 x 2257	680	400	2"
01011300047	15,000	4050 x 2240 x 2257	680	650	2"



2 FRONT AND REAR OUTLETS

- Manhole fitted as standard
- Thickness: 8 - 10 mm
- 300 - 1700 L: vent in the cover
- From 2750 L upwards: vents and sleeves supplied separately

OPTIONS

Reference	Description
01990900011	1" 1/4 PVC valve
01990900001	2" PVC valve



sale of agricultural equipment by telephone

00 333 88 70 91 29

BEISER Environnement • Domaine de la Reidt
67330 BOUXWILLER • France
Fax: 00 333 88 71 34 64