

Basic industrial fuel station

Fuel station

TANKS

OPTION
EXTENDED WARRANTY FOR THE PUMP
1-year - 2-year - 3-year



OPTION
EXTENDED WARRANTY FOR THE TANK
2-year - 5-year - 10-year

info
For fuel storage and fuel distribution, locking device

Non-contractual photo

TECHNICAL CHARACTERISTICS

HDPE fuel tank with metal reinforcements; meets the requirements of NF standards

Fuel pump 60L/min, 220 V, with:

8 m suction and discharge hoses

Automatic gun

Flowmeter with summer

Differential circuit breaker

Gauge

Filling plug

Diesel filter water settling tank

Cabinet:

Lock up your pumping equipment

Restrict access to authorised individuals

Retention tray with:

2 securing points

Padlock-compatible tipup cover

Base with fork slots

External and internal rustproof coating, RAL 6000

The small retention tray with its thickness of 3 mm protects the tank against any impact or vandalism.

It can also be used to ensure compliance with standards on pollutant products

Reference	Capacity in Litres	L in mm	W in mm	H in mm
01020702001	1000	1200	810	1650
01020702002	1500	1750	830	1650
01020702003	2000	2200	850	1650
01020702004	2500	2350	1000	1500
01020702005	5000	2350	2000	1500

ON-LINE QUOTES
www.beiser-se.com
AND PURCHASING



DETAILS

- ① HDPE fuel tank with metal reinforcements
- ② 1 cabinet with lock, to secure pumping equipment
- ③ Padlock-compatible tipup cover
- ④ Base with fork slots
- ⑤ Pump, 220 V, 60 L/min



FREE DELIVERY*
*Offers subject to conditions

BEISER
environnement

sale of agricultural equipment by telephone

00 333 88 70 91 29